



Submittal: SDWSWH1232Z



STRONG-POINT® UNSLOTTED INDENTED HEX WASHER HEAD, ZINC PLATED W/BONDED NEO-EPDM WASHER

Size	Part#	Pt.	Case Qty.	Description				
12-14 x 2 HA1232 3 1.		1.5M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer					
12-14 x 2-1/2	HA1240	3	1M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer				
12-14 x 3	HA1248	3	1M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer				
12-14 x 4	HA1264	3	.5M	Unslotted Indented Hex Washer Head, Zinc Plated w/Bonded NEO-EPDM Washer				

Application: Attaches

Attaches metal to metal.

Drill Capacity (in.): .035 - .210

Specifications:

- Meets ASTM¹ C 1513 for cold-formed steel framing connections
- Meets ASTM A 510 for carbon steel manufacturing
- Manufactured to SAE² J78 for dimensional specifications
- Meets F.I.P.³-1000.7 for torsional strength and drill speed
- Meets ASTM F1941 for corrosion resistance
- ICC-ES Evaluation Report: ESR-3528

Installation:

A 5/16" hex nut setter or 5/16" drive socket with torque limiting nose piece set at a maximum of 2000 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

Pullout Values (Avg. Lbs.)											
Fastener		Steel Gauge									
Size	Pt.	22	20	18	16	14	12	1/8	3/16		
12-14	3	283	333	537	737	1034	1585	2349	2911		

				Shear Value	s (Avg. Lbs.)						
Fastener		Steel Gauge (Lapped)									
Size	Pt.	22	20	18	16	14	12	1/8	3/16		
12-14	3		749	1320	1574	1914	1929				

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

1(American Society of Testing Materials)

²(Society of Automotive Engineers)

3(Fastener Inspection Products)

HA1232_HA1264_Rev. A (5/27/15)

Los Angeles **New York** Chicago **Dallas Atlanta Portland** Houston Cleveland Miami 800.558.7222 800.533.9669 800.762.2004 888.322.2262 800.533.9669 800.558.7222 800.822.9690 800.434.5606 800.822.9690