



Submittal: SD4SWH1412BS





${\tt STRONG-POINT}^{\circledast}~410~{\tt STAINLESS}~{\tt STEEL}~{\tt UNSLOTTED}~{\tt INDENTED}~{\tt HEX}~{\tt WASHER}~{\tt HEAD},~{\tt PASSIVATED}~\&~{\tt WAXED}~{\tt W/BONDED}~{\tt NEO-EPDM}~{\tt WASHER}$

Size	Part#	Pt.	Case Qty.	Description						
14-14 x 3/4	4HA1412	3	3M	Unslotted Indented Hex Washer Head, Passivated & Waxed w/Bonded NEO-EPDM Washe						
14-14 x 1	4HA1416	3	2.5M	Unslotted Indented Hex Washer Head, Passivated & Waxed w/Bonded NEO-EPDM Wash						
14-14 x 1-1/4	4HA1420	3	2M	Unslotted Indented Hex Washer Head, Passivated & Waxed w/Bonded NEO-EPDM Washer						
14-14 x 1-1/2	4HA1424	3	1.5M	Unslotted Indented Hex Washer Head, Passivated & Waxed w/Bonded NEO-EPDM Washer						
14-14 x 2	4HA1432	3	1M	Unslotted Indented Hex Washer Head, Passivated & Waxed w/Bonded NEO-EPDM Washer						
Application:	Attaches metal to metal. Drill Capacity (in.): .060220									
Specifications:	• Meets F.I.P.2	-1000.7 fo		nal specifications gth and drill speed						

Installation:

A 3/8" hex nut setter or 3/8" drive socket with torque limiting nose piece set at a maximum of 1750 RPM drive speed recommended. Do not over torque as it can cause the head to snap or stripping of the threads. Installed fasteners must penetrate a minimum of three full threads beyond the metal structure.

				Pullout	Values (Av	g. Lbs.)						
Fastener			Steel Gauge									
Size	Pt.	22	20	18	16	14	12	1/8	3/16	1/4		
14-14	3	287	339	595	856	1114	1805	2337	4416	4885		

				Shear	Values (Avg	. Lbs.)						
Fastener			Steel Gauge (Lapped)									
Size	Pt.	22	20	18	16	14	12	1/8	3/16	1/4		
14-14	3		905	1401	2040	2509	2573	2738				

The values listed are averages achieved under laboratory conditions and imply no warranty. Appropriate safety factors should be applied to these values for design purposes.

1(Society of Automotive Engineers)

²(Fastener Inspection Products)

4HA1412_4HA1432_Rev. A (7/7/15)