

## Asbestos-Free Duct Sealer



<b>Base:</b>	Non-drying synthetic polymers & oils
<b>Color:</b>	Gray
<b>Application Temp:</b>	25 to 120 °F (-4 to 49 °C)
<b>Operating Temp:</b>	-30 to 175 °F (-34 to 80 °C)
<b>Dielectric Strength:</b>	100 volts/mil (ASTM D149-64)
<b>Flame Resistant:</b>	Flame Spread - 5 Smoke Developed - 10

### Applications

- Sealing electrical conduit openings and joints against water infiltration
- Sealing around steel conduits where they enter an exposed junction
- Sealing against water and dirt in electrical pot heads, terminal boxes, electrical bushings, and more
- Dampening panel noise and vibration in switch gear

### Features

- Polymer/Oil Blend

### Benefits

- Adheres to a variety of surfaces
- Non-Staining
- Paintable
- Excellent resistance to water, alcohols, mild acids and bases
- Excellent aging characteristics - will not dry out over time
- Tested in accordance with UL 723

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.